



**Rubber Tubing, Chloroprene**

• **Helsyn H**

**Features and Benefits**

The high elasticity of the material ensures many cable diameters can be covered with one size of sleeve.

Can withstand up to 120°C intermittent temperature.

**Application**

The chloroprene tubings (H) are ideally suited to rigorous environments such as aerospace, mass transit and defence markets.

As the material is highly elastic, its original size can be expanded 500% on application and 200% in continuous use.

To save time and effort when fitting the tubing, try the HellermannTyton K, S and SS three prong tools (see Chapter 6.3) and the Hellerrine lubricant (see Chapter 2.3), which are specially designed for use with HellermannTyton chloroprene tubing.



*H rubber tubing is highly flexible and easy to apply.*

**Other colours and cut lengths available on request. Please contact us!**

**Material Data**


Material	<b>Chloroprene (CR)</b>
Operating Temperature	<b>-65 °C to +95 °C, Intermittent 120 °C</b>
Flammability	<b>UL94 HB</b>
Specification	<b>BS 3858 Type 1, IEC 684-3-116, BS 4 G 198 Part 1 Type 1, DEF STAN 59-15 D2</b>



**Technical Table**

Article-No.	Type	Colour	Ø D	Wall (WT) nom.	Pack Cont. (pcs./bag)
600-01520	<b>H12</b>	Black (BK)	1.2	0.70	1000
600-01600	<b>H15</b>	Black (BK)	1.5	0.80	1000
600-01700	<b>H20</b>	Black (BK)	2.0	0.80	1000
600-01841	<b>H30</b>	Black (BK)	3.0	0.80	1000
600-01982	<b>H50</b>	Black (BK)	5.0	1.00	1000
600-02063	<b>H75</b>	Black (BK)	7.5	1.30	1000
600-02105	<b>H100</b>	Black (BK)	10.0	1.50	1000
600-02155	<b>H150</b>	Black (BK)	15.0	1.70	1000

All dimensions in mm. Subject to technical changes.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.