



Heat Shrinkable Tubing 2:1 flexible and transparent

- TF24

Features and Benefits

TF24 transparent tubing is ideal to protect wire and cable markers. The transparency allows for the inspectability of the substrate covered. TF24 is halogen free.



TF24 – ideal to protect cable markers.

Cut lengths available on request. Please contact us!

Material Data

Material	Polyolefin, cross-linked (POX)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +135 °C
Minimum Shrink Temperature	+110 °C
Longitudinal change after shrinkage	+/-5% max.
Dielectric Strength	46 kV/mm
Specification	VG 95343, SAE - AMS - DTL-23053/5 Class 2, DEF STAN 59-97 Type 2B



Technical Table

Article-No.	Type	Designation as per VG-Norm	Wall (WT) nom.	Supplied Ø D	Recov. Ø d	Colour	Reel Length (m)
309-40123	TF24-1.2/0.6	VG95343T05B001M	0.41	1.2	0.6	Transparent (CL)	100
309-40163	TF24-1.6/0.8	VG95343T05B002M	0.43	1.6	0.8	Transparent (CL)	100
309-40243	TF24-2.4/1.2	VG95343T05B003M	1.51	2.4	1.2	Transparent (CL)	100
309-40323	TF24-3.2/1.6	VG95343T05B004M	0.51	3.2	1.6	Transparent (CL)	100
309-50483	TF24-4.8/2.4	VG95343T05B005M	0.51	4.8	2.4	Transparent (CL)	60
309-50643	TF24-6.4/3.2	VG95343T05B006M	0.64	6.4	3.2	Transparent (CL)	60
309-40953	TF24-9.5/4.8	VG95343T05B007M	0.64	9.5	4.8	Transparent (CL)	50
309-41273	TF24-12.7/6.4	VG95343T05B008M	0.64	12.7	6.4	Transparent (CL)	50
309-31903	TF24-19.1/9.5	VG95343T05B009M	0.76	19.1	9.5	Transparent (CL)	50
309-32543	TF24-25.4/12.7	VG95343T05B010M	0.89	25.4	25.4	Transparent (CL)	50
309-33813	TF24-38.1/19.1	VG95343T05B011M	1.02	38.1	19.1	Transparent (CL)	60
309-35083	TF24-50.8/25.4	VG95343T05B012M	1.14	50.8	25.4	Transparent (CL)	60
309-37603	TF24-76.2/38.1	VG95343T05B013M	1.27	76.2	38.1	Transparent (CL)	30
309-31023	TF24-101.6/50.8	VG95343T05B014M	1.40	101.6	50.8	Transparent (CL)	15

All dimensions in mm. Subject to technical changes.



Please note! Not all products listed on this page may have this approval. For product specific approvals please refer to the Appendix.