


X2-SERIES – RUGGED USB CONNECTIONS

USB A – JAM NUT DUAL RECEPTACLE WITH CORDSET X2-9865



INFORMATION

All dimensions in
mm (inch) unless
otherwise specified.

Shell derived from D38999

PN: X2-9865

Datasheet Version: 1.0

CATALOG:

Harsh Environment
Data Connectivity Solutions



Table A: Material & Plating

Material & Plating Code	Technical Design	ROHS-/REACH Compliant	Electrically Conductive	Salt Spray Resistance according to MIL spec.	Salt Spray Resistance according to VG spec.
V	Tin-Zinc grey Base material: Al-alloy Tin-Zinc over electroless Nickel	Yes	Yes	500 hrs	5 day cyclic
5	Electroless Nickel Base material: Al-alloy	Yes	Yes	48 hrs	n.a.
2	Zinc-Nickel black Coupling ring: Al-alloy, black anodized Shell: Zinc-Nickel black chromate over electroless Nickel	Yes	Yes	500 hrs	n.a.
6	Cadmium olive drab Coupling ring: Al-alloy, olive drab anodized Shell: Al-alloy Cadmium plated olive drab over electroless Nickel	No	Yes	500 hrs	5 day cyclic
9	Marine Bronze Base material: Marine Bronze CuAl10Ni5Fe4 (CW307G) Shotblast, nonreflective	Yes	Yes	n.a.	n.a.
1	Stainless Steel / passivated	Yes	Yes	n.a.	n.a.

Performance

Voltage Rating (V_BUS)	20 V
Current Rating (V_BUS)	3 A
Temperature	-20 °C to +85 °C
Mating cycles (USB A)	>5.000
Compatible with	USB 3.2 Gen 1

Materials

Over molding (plug)	PVC
USB A shell	Nickel plated
Cable jacket	PVC
Cable type	UL 2725
Housing	See option material

For details about panel cut out see page 72-75 in the full „Harsh Environment Data Connectivity Solutions“ catalog.

Table B: Cable length

Length Code	Length L in mm	Tolerance in mm
0500	500 (19.685)	+ 30 (1.181)
1000	1000 (39,370)	+ 40 (1.575)

How to order

	Table	X2-9865	15	5	0500
Basic part number					
Shell size					
Material & plating code	A				
Cable length	B				

ORDER EXAMPLE

X2-9865-15-5-0500

USB A DUAL – JAM NUT WITH CORDSET
 SIZE 15
 ELECTROLESS NICKEL
 CABLE LENGTH 500 MM

EMCA CONNECTOR SOLUTIONS GMBH

X2-9865 | Datasheet Version 1.0

SALES@EMCA-CONNECTOR.DE